

### Overview

#### Models

HP MSR20-10 Router	JD431A
HP MSR20-11 Router	JF239A
HP MSR20-12 Router	JF241A
HP MSR20-12-W Router	JF807A
HP MSR20-12-T Router	JF806A
HP MSR20-12-T-W Router (NA)	JG209A
HP MSR20-13 Router	JF240A
HP MSR20-13-W Router	JF808A
HP MSR20-13-W Router (NA)	JG210A
HP MSR20-15-A Router	JF237A
HP MSR20-15-A-W Router	JF809A
HP MSR20-15-I Router	JF236A
HP MSR20-15-I-W Router	JF238A
HP MSR20-15 Router	JF817A

#### Key features

- Routing, switching, security, wireless, and voice
- Compact design for both desktop and rackmounting
- Fixed-port and modular WAN/LAN interface options
- Embedded encryption, firewall, security features
- Single-pane-of-glass management

#### Product overview

The HP MSR20-1x Series is a component of the HP FlexBranch solution, which is part of the HP FlexNetwork architecture. MSR20-1X routers are full-featured, economical routers designed for converged wired and wireless WAN and LAN environments at small remote branch offices and small to medium-sized businesses. HP MSR20-1x series routers deliver high-performance integrated routing, switching, security, wireless, and voice services while reducing complexity, simplifying management, and increasing control. These routers enable an agile and flexible network infrastructure that can quickly adapt to changing business requirements while delivering integrated services on a single, easy-to-manage platform.

#### Features and benefits

##### Quality of Service (QoS)

- **Traffic policing:** supports Committed Access Rate (CAR) and line rate
- **Congestion management:** supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- **Congestion avoidance:** Weighted Random Early Detection (WRED)/Random Early Detection (RED)
- **Other QoS technologies:** support traffic shaping, FR QoS, MPLS QoS, and MP QoS/LFI

##### Management

- **Industry-standard CLI with a hierarchical structure:** reduces training time and expenses, and increases productivity in multivendor installations

### Overview

- **Management security:** multiple privilege levels with password protection restrict access to critical configuration commands; ACLs provide telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- **SNMPv1, v2, and v3:** provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support:** FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)
- **Debug and sampler utility:** supports ping and traceroute for both IPv4 and IPv6
- **Network Time Protocol (NTP):** synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Info center:** provides a central information center for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules
- **Management interface control:** provides management access through modem port and terminal interface; provides access through terminal interface, telnet, or SSH
- **Network Quality Analyzer (NQA):** analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays; allows network manager to determine overall network performance and diagnose and locate network congestion points or failures

### Connectivity

- **Packet storm protection:** protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Loopback:** supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **3G access support:** provides 3G wireless access for primary or backup connectivity via a 3G SIC module certified on various cellular networks; optional carrier 3G USB modems available
- **Flexible port selection:** provides a combination of fiber and copper interface modules, 100/1000BASE-X auto-speed selection, and 10/100/1000BASE-T auto-speed detection plus auto duplex and MDI/MDI-X
- **Multiple WAN interfaces:** provide a traditional link with E1, T1, ADSL, ADSL2, ADSL2+, G.SHDSL, ATM, Serial, and ISDN/AM backup; provide high-density Ethernet access with WAN Fast Ethernet/Gigabit Ethernet and LAN 4- and 9-port Fast Ethernet; provide mobility access with 802.11b/g/n Wi-Fi and 3G
- **High-density port connectivity:** includes one interface module slot and up to 10 Fast Ethernet ports

### Performance

- **Powerful encryption capacity:** includes embedded hardware encryption accelerator to improve encryption performance
- **Flexible chassis selection:** offers a choice of 12 routers, meeting different requirements on enterprise branches
- **Excellent forwarding performance:** provides forwarding performance up to 160 Kpps; meets current and future bandwidth-intensive application demands of enterprise businesses

### Resiliency and high availability

- **Backup Center:** acts as a part of the management and backup function to provide backup for device interfaces; delivers reliability by switching traffic over to a backup interface when the primary one fails
- **Virtual Router Redundancy Protocol (VRRP):** allows groups of two routers to dynamically back each other up to create highly available routed environments; supports VRRP load balancing

### Overview

#### Layer 2 switching

- **Spanning Tree Protocol (STP)**  
fully supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network
- **Port mirroring:** duplicates port traffic (ingress and egress) to a local or remote monitoring port
- **VLANs:** support IEEE 802.1Q-based VLANs
- **sFlow:** allows traffic sampling

#### Layer 3 services

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper:** redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

#### Layer 3 routing

- **Static IPv4 routing**  
provides simple, manually configured IPv4 routing
- **Routing Information Protocol (RIP)**  
uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- **Open Shortest Path First (OSPF)**  
Interior Gateway Protocol (IGP) uses link-state protocol for faster convergence; supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Border Gateway Protocol 4 (BGP-4)**  
Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks
- **Intermediate system to intermediate system (IS-IS)**  
Interior Gateway Protocol (IGP) uses path vector protocol, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Static IPv6 routing**  
provides simple, manually configured IPv6 routing
- **Dual IP stack**  
maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design
- **Routing Information Protocol next generation (RIPng)**  
extends RIPv2 to support IPv6 addressing
- **OSPFv3**  
provides OSPF support for IPv6
- **BGP+**  
extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **IS-IS for IPv6**  
extends IS-IS to support IPv6 addressing
- **IPv6 tunneling**

### Overview

is an important element for the transition from IPv4 to IPv6; allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels

- **Multiprotocol Label Switching (MPLS)**

uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, thus reducing complexity and increasing performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks

- **Multiprotocol Label Switching (MPLS) Layer 3 VPN**

allows Layer 3 VPNs across a provider network; uses Multiprotocol BGP (MP-BGP) to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility; supports IPv6 MPLS VPN

- **Multiprotocol Label Switching (MPLS) Layer 2 VPN**

establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP); requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies

- **Policy routing**

allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

### Security

- **Access control list (ACL):** supports powerful ACLs for both IPv4 and IPv6; ACLs are used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can be set to operate on specific dates or times
- **TACACS+:** is an authentication tool using TCP with encryption of the full authentication request that provides additional security
- **Network login:** standard IEEE 802.1x allows authentication of multiple users per port
- **RADIUS:** eases security access administration by using a password authentication server
- **Network address translation (NAT):** supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT-PT to support multiple connections; supports blacklist in NAT/NAT-PT, a limit on the number of connections, session logs, and multi-instances
- **Secure Shell (SSHv2):** uses external servers to securely login into a remote device or securely login into MSR from a remote location; with authentication and encryption, it protects against IP spoofing and plain text password interception; increases the security of SFTP transfers
- **Unicast Reverse Path Forwarding (URPF):** allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks
- **IPSec VPN:** supports DES, 3DES, and AES 128/192/256 encryption, and MD5 and SHA-1 authentication
- **DVPN (Dynamic Virtual Private Network):** collects, maintains, and distributes dynamic public addresses through the VPN Address Management (VAM) protocol, making VPN establishment available between enterprise branches that use dynamic addresses to access the public network; compared to traditional VPN technologies, DVPN technology is more flexible and has richer features, such as NAT traversal of DVPN packets, AAA identity authentication, IPSec protection of data packets, and multiple VPN domains

### Convergence

- **Internet Group Management Protocol (IGMP):** is used by IP hosts to establish and maintain multicast groups; supports IGMPv1, v2, and v3; utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- **Protocol Independent Multicast (PIM):** is used for IPv4 and IPv6 multicast applications; supports PIM Dense Mode (PIM-DM), Sparse Mode (PIM-SM), and Source-Specific Mode (PIM-SSM)
- **Multicast Source Discovery Protocol (MSDP):** is used for inter-domain multicast applications, allowing multiple PIM-SM domains to interoperate

### Overview

- **Multicast Border Gateway Protocol (MBGP):** allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic

### Integration

- **Embedded NetStream:** local and global server load-balancing module improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services; monitors the health status of servers and firewalls
- **Embedded VPN firewall:** provides enhanced stateful packet inspection and filtering; delivers advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement

### Additional information

- **OPEX savings:** are delivered through the use of a common operating system that simplifies and streamlines deployment, management, and training, thereby cutting costs as well as reducing the chance for human errors associated with having to manage multiple operating systems across different platforms and network layers
- **High reliability:** provides a state-of-the-art unified code base
- **Faster time to market:** engineering efficiencies allow new and custom features to be brought rapidly to the market with better initial and ongoing stability
- **Green initiative support:** provides support for RoHS and WEEE regulations

### Product architecture

- **Ideal multiservice platform:** provides WAN router, Ethernet switch, wireless LAN, 3G WAN, firewall, VPN, and SIP/voice gateway all in one box
- **High-density voice interfaces:** provide flexible analog and digital voice interface options for easy integration within a wide range of deployments
- **USB interface:** uses USB memory disk to download and upload configuration files; supports external USB 3G modem for 3G WAN uplink
- **Flexible modular design:** includes multiple types of modules that meet different requirements, such as Smart Interface Cards (SICs), which are small and cost-effective modules; Multi-functional Interface Modules (MIMs), which are more high-density and affordable modules; Flexible Interface Cards (FICs), which provide high reliability and are hot-swappable; and double-width modules, which provide high density

### Warranty and support

- **1-year warranty:** with advance replacement and delivery (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases:** to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

### Configuration

#### Build To Order:

**BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.**

##### HP MSR20-10 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot

JD431A  
[See Configuration](#)  
Note:1, 2, 9

##### Russian Reduced Encryption

JD431A#A59

##### HP MSR20-11 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot

JF239A  
[See Configuration](#)  
Note:1, 2, 9

##### Russian Reduced Encryption

JF239A#A59

##### HP MSR20-12 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF241A  
[See Configuration](#)  
Note:1, 2, 9

##### Russian Reduced Encryption

JF241A#A59

##### HP MSR20-12-T Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF806A  
[See Configuration](#)  
Note:1, 2, 9

##### Russian Reduced Encryption

JF806A#A59

##### HP MSR20-12-W Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF807A  
[See Configuration](#)  
Note:1, 2, 9

### Configuration

Russian Reduced Encryption	JF807A#A59
HP MSR20-13 Router	JF240A
<ul style="list-style-type: none"><li>• 1 - SIC module slot</li><li>• 1 - 256MB DDR SDRAM included</li><li>• 0 - ESM Slot</li><li>• 0 - VCPM slots</li><li>• 0 - VPM slot</li></ul>	See Configuration Note:1, 2, 9
Russian Reduced Encryption	JF240A#A59
HP MSR20-13-W Router	JF808A
<ul style="list-style-type: none"><li>• 1 - SIC module slot</li><li>• 1 - 256MB DDR SDRAM included</li><li>• 0 - ESM Slot</li><li>• 0 - VCPM slots</li><li>• 0 - VPM slot</li></ul>	See Configuration Note:1, 2, 9
Russian Reduced Encryption	JF808A#A59
HP A-MSR20-13-W Router (NA)	JG210A
<ul style="list-style-type: none"><li>• 1 - SIC module slot</li><li>• 1 - 256MB DDR SDRAM included</li><li>• 0 - ESM Slot</li><li>• 0 - VCPM slots</li><li>• 0 - VPM slot</li></ul>	See Configuration Note:1, 9
HP MSR20-15-A-W Router	JG209A
<ul style="list-style-type: none"><li>• 1 - SIC module slot</li><li>• 1 - 256MB DDR SDRAM included</li><li>• 0 - ESM Slot</li><li>• 0 - VCPM slots</li><li>• 1 - VPM slot</li></ul>	See Configuration Note:1, 9
HP MSR20-15-I Router	JF236A
<ul style="list-style-type: none"><li>• 1 - SIC module slot</li><li>• 1 - RJ-45 ADSL2+ port</li><li>• 1 - ISDN port</li><li>• 1 - 256MB DDR SDRAM included</li><li>• 0 - ESM Slot</li><li>• 0 - VCPM slots</li><li>• 1 - VPM slot</li></ul>	See Configuration Note:1, 2, 9
Russian Reduced Encryption	JF236A#A59
HP MSR20-15-A-W Router	JF809A

### Configuration

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

See Configuration  
Note:1, 2, 9

Russian Reduced Encryption

JF809A#A59

HP MSR20-15-A Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF237A  
See Configuration  
Note:1, 2, 9

Russian Reduced Encryption

JF237A#A59

HP MSR20-15-I-W Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot

JF238A  
See Configuration  
Note:1, 2, 9

Russian Reduced Encryption

JF238A#A59

HP MSR20-15 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF817A  
See Configuration  
Note:1, 2, 9

Russian Reduced Encryption

JF817A#A59

### Configuration Rules:

Note 1 AC Power Supply included

Note 2 If this product is ordered for delivery to Russia, it must be ordered with the A59 option (also allowed for other countries desiring Low Encryption), then #A59 is the required option in addition to Localization options.

Note 9 Localization required. (See Localization Menu)

## Internal Power Supplies

Internal Power Supplies included



### Configuration

#### Modules

##### SIC Modules

HP MSR 4-port 10/100 SIC Module	JD573B
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 9-port 10/100 DSIC Module	JD574B
	<a href="#">See Configuration Note:2</a>
HP MSR 1-port 10/100 SIC Module	JD545B
<ul style="list-style-type: none"><li>• None</li></ul>	
HP 1-port 100Mbt SFP SIC Router Module	JF280A
<ul style="list-style-type: none"><li>• min=0 \ max=1 SFP Transceivers</li></ul>	<a href="#">See Configuration Note:4</a>
HP MSR 1-port 10/100/1000 SIC Module	JD572A
<ul style="list-style-type: none"><li>• min=0 \ max=1 SFP Transceivers</li></ul>	<a href="#">See Configuration Note:5</a>
HP MSR 2-port FXO SIC Module	JD558A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 1-port FXO SIC Module	JD559A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 2-port FXS SIC Module	JD560A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 1-port FXS SIC Module	JD561A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 1-port E1-Voice SIC Module	JD575A
<ul style="list-style-type: none"><li>• min=0 \ max=1 E1 Cable</li></ul>	<a href="#">See Configuration Note:1, 6, 11</a>
HP MSR 1-port T1-Voice SIC Module	JD576A
<ul style="list-style-type: none"><li>• min=0 \ max=1 E1 Cable</li></ul>	<a href="#">See Configuration Note:1, 7</a>
HP 2p ISDN-S/T Voice Interface SIC Mod	JF821A
<ul style="list-style-type: none"><li>• None</li></ul>	

### Configuration

HP MSR 2FXS + 1FXO Voice Intfc SIC Mod	JD632A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 1-port Fractional E1 SIC Module	JD634B
<ul style="list-style-type: none"><li>• min=0 \ max=1 E1 Cable</li></ul>	See Configuration Note:6
HP MSR 1-port Fractional SIC Module	JD538A
<ul style="list-style-type: none"><li>• None</li></ul>	See Configuration Note:7
HP MSR 2-port Fractional E1 SIC Module	JF842A
<ul style="list-style-type: none"><li>• None</li></ul>	See Configuration Note:10, 12
HP MSR 1-port Enhanced Serial SIC Mod	JD557A
<ul style="list-style-type: none"><li>• None</li></ul>	See Configuration Note:8
HP A-MSR 1-port ADSL over POTS SIC Module	JD537A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 1-port ISDN-S/T SIC Module	JD571A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP A-MSR 8-port Async Serial SIC Module	JF281A
<ul style="list-style-type: none"><li>• Must select 1 8AS Communication Cable (min=1 \ max=1 cable)</li></ul>	See Configuration Note:9
HP 802.11b/g/n Wireless AP SIC Module	JF819A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 802.11b/g/n Wless AP SIC Mod (NA)	JG211A
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 1p 8-wire G.SHDSL (RJ45) DSIC Mod	JG191A
<ul style="list-style-type: none"><li>• None</li></ul>	See Configuration Note:2
HP MSR 1-port ADSL over ISDN SIC Module	JG056B
<ul style="list-style-type: none"><li>• None</li></ul>	
HP MSR 16-port Async Serial SIC Module	JG186A
<ul style="list-style-type: none"><li>• Must select 4 HP X260 mini D-28/4-RJ45 0.3m Rtr Cables (min=4 \ max=4 cables)</li></ul>	See Configuration Note:9, 10

### Configuration

HP A-MSR 4-port FXS/1-port FXO DSIC Mod

- None

JG189A  
See Configuration  
Note:2

HP A-MSR HSPA/WCDMA SIC Module

- None

JG187A

### Configuration Rules:

Note 1	These Modules are NOT supported on the following routers: HP A-MSR20-10 Router HP A-MSR20-11 Router HP A-MSR20-13 Router HP A-MSR20-13-W Router HP A-MSR20-13-W Router (NA)	JD431A JD239A JD240A JF808A JF210A
Note 2	This Module takes up one slot on this router. (Special Slot)	
Note 4	The following Transceivers install into this Module: HP X110 100M SFP LC LH40 Transceiver HP X110 100M SFP LC LH80 Transceiver HP X110 100M SFP LC FX Transceiver HP X110 100M SFP LC LX Transceiver	JD090A JD091A JD102B JD120B
Note 5	The following Transceivers install into this Module: HP X125 1G SFP LC LH70 Transceiver HP X120 1G SFP LC LH40 1550nm Transceiver HP X125 1G SFP LC LH40 1310nm Transceiver HP X120 1G SFP LC LH100 Transceiver HP X120 1G SFP LC SX Transceiver HP X120 1G SFP LC LX Transceiver	JD063B JD062A JD061A JD103A JD118B JD119B
Note 6	The following E1 Cables install into this Module: HP X260 E1 (2) BNC 75 ohm 3m Rtr Cable HP X260 E1 BNC 20m Router Cable HP X260 E1/2 BNC 75 ohm 40m Router Cable	JD175A JD514A JD516A
Note 7	The following T1 Cables install into this Module: T1 Cable RJ45/RJ45-3m	JD518A
Note 8	The following Cables install into this Module: V.24 Serial Port Cable, DTE, 3m V.24 Serial Port Cable, DCE, 3m V.35 Serial Port Cable, DTE, 3m V.35 Serial Port Cable, DCE, 3m	JD519A JD521A JD523A JD525A

### Configuration

X.21 Serial Port Cable, DTE, 3m	JD527A
X.21 Serial Port Cable, DCE, 3m	JD529A
RS449 Serial Port Cable, DTE, 3m	JF825A
RS449 Serial Port Cable, DCE, 3m	JF826A
RS530 Serial Port Cable, DTE, 3m	JF827A
RS530 Serial Port Cable, DCE, 3m	JF828A

Note 9 If this module is selected Then 1 JD642A - HP X260 SIC-8AS RJ45 0.28m Router Cable is required.

Note 10 If this module is selected Then 4 - JG263A HP X260 mini D-28/4-RJ45 0.3m Rtr Cable are required to be on the same order.

Note 11 The following E1 Cables install into this Module:

HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 RJ45 20m Router Cable	JD517A

Note 12 The following 2E1 Cables install into this Module:

HP X260 2E1 BNC 3m Router Cable	JD643A
---------------------------------	--------

### Voice Processing Modules

JF241A, JF806A, JF807A, JG209A, JF236A, JF809A, JF237A, JF238A, JF817A Only - System (std 0 // max 2) User Selection (min 0 // max 2)

HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A

### Transceivers

#### SFP Transceivers

HP X115 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LH40 Transceiver	JD120B
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B

### Configuration

HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B

### Cables

HP X260 mini D-28/4-RJ45 0.3m Rtr Cable	JG263A
HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A
HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A
HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 E1 (2) BNC 75 ohm 3m Rtr Cable	JD175A

### Configuration

HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1/2 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Router Cable	JD518A
HP X260 T1 Voice Router Cable	JD535A
HP X260 T3/E3 Router Cable	JD531A
HP X260 E3-30 E3/T3 Router Cable	JD533A
HP X260 E1 4-port IMA Router Cable	JD638A
HP X260 8E1 BNC 75 ohm 3m Router Cable	JD512A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A
HP X200 Transit Plug D25F MP8(S) Single Cable	JD636A
HP X200 Transit Cable RJ45 0.5m Single Cable	JD641A

#### Remarks:

The following cable is used for RJ45 BNC Conversion -  
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable

JD511A

### Router Options

#### Compact Flash cards

System (std 0 // max 1) User Selection (min 0 // max 1)

HP 7500 1G Compact Flash Card	JC684A
HP 7500 512M Compact Flash Card	JC685A
HP 7500 256MB Compact Flash Card	JC686A

#### Mount Angle Components

System (std 0 // max 1) User Selection (min 0 // max 1)



## Configuration

HP A3100/E4210-16/-8 POE Rack Mount Kit

JD323A

### Technical Specifications

#### HP MSR20-10 Router (JD431A)

<b>Ports</b>	1 S1C slot 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in. (30 x 24 x 4.42 cm) (1U height) <b>Weight</b> 6.61 lb (3.0 kg)
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<b>Throughput</b> up to 160 Kpps (64-byte packets) <b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)
<b>Environment</b>	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C) <b>Operating relative humidity</b> 5% to 90%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b> 85 BTU/hr (89.68 kJ/hr) <b>Voltage</b> 100-120/200-240 VAC <b>Maximum power rating</b> 25 W <b>Frequency</b> 50/60 Hz <b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B
<b>Telecom</b>	FCC part 68; CS-03

### Technical Specifications

<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Weight is with no optional modules installed.
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (UW075E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)</p> <p>3-year, 24x7 SW phone support, software updates (UW012E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)</p> <p>4-year, 24x7 SW phone support, software updates (UW013E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)</p> <p>5-year, 24x7 SW phone support, software updates (UW014E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW079E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW080E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW081E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)</p> <p>1-year, 24x7 software phone support, software updates (HR557E)</p>
	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### HP MSR20-11 Router (JF239A)

<b>Ports</b>	<p>1 SIC slot</p> <p>1 Serial port</p> <p>1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p> <p>4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p>
<b>Physical characteristics</b>	<p><b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</p> <p><b>Weight</b> 6.61 lb (3 kg)</p>
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<p><b>Throughput</b> up to 160 Kpps (64-byte packets)</p> <p><b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)</p>

### Technical Specifications

<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	5% to 95%, noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)
	<b>Voltage</b>	100-120/200-240 VAC
	<b>Maximum power rating</b>	25 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B	
<b>Telecom</b>	FCC part 68; CS-03	
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Weight is with no optional modules installed.	
<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)	

### Technical Specifications

- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-12 Router (JF241A)

<b>Ports</b>	1 SIC slot 1 E1 port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height) <b>Weight</b> 6.61 lb (3.0 kg)
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<b>Throughput</b> up to 160 Kpps (64-byte packets) <b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)
<b>Environment</b>	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C) <b>Operating relative humidity</b> 5% to 90%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b> 85 BTU/hr (89.68 kJ/hr) <b>Voltage</b> 100-120/200-240 VAC <b>Maximum power rating</b> 25 W <b>Frequency</b> 50/60 Hz

### Technical Specifications

**Notes** Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B
<b>Telecom</b>	FCC part 68; CS-03
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.
<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E) 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions

### Technical Specifications

and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-12-W Router (JF807A)

<b>Ports</b>	1 SIC slot 1 E1 port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full										
<b>AP characteristics</b>	<table border="0"> <tr> <td><b>Radios</b></td> <td>Single (b/g)</td> </tr> <tr> <td><b>Radio operation modes</b></td> <td>Client access</td> </tr> <tr> <td><b>AP operation modes</b></td> <td>Autonomous</td> </tr> <tr> <td><b>Wi-Fi Alliance Certification*</b></td> <td>b/g Wi-Fi Certified</td> </tr> </table> <p>* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing preformed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.</p>	<b>Radios</b>	Single (b/g)	<b>Radio operation modes</b>	Client access	<b>AP operation modes</b>	Autonomous	<b>Wi-Fi Alliance Certification*</b>	b/g Wi-Fi Certified		
<b>Radios</b>	Single (b/g)										
<b>Radio operation modes</b>	Client access										
<b>AP operation modes</b>	Autonomous										
<b>Wi-Fi Alliance Certification*</b>	b/g Wi-Fi Certified										
<b>Physical characteristics</b>	<table border="0"> <tr> <td><b>Dimensions</b></td> <td>11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</td> </tr> <tr> <td><b>Weight</b></td> <td>6.61 lb (3.0 kg)</td> </tr> </table>	<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)	<b>Weight</b>	6.61 lb (3.0 kg)						
<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)										
<b>Weight</b>	6.61 lb (3.0 kg)										
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash										
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.										
<b>Performance</b>	<table border="0"> <tr> <td><b>Throughput</b></td> <td>up to 160 Kpps (64-byte packets)</td> </tr> <tr> <td><b>Routing table size</b></td> <td>10000 entries (IPv4), 10000 entries (IPv6)</td> </tr> </table>	<b>Throughput</b>	up to 160 Kpps (64-byte packets)	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)						
<b>Throughput</b>	up to 160 Kpps (64-byte packets)										
<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)										
<b>Environment</b>	<table border="0"> <tr> <td><b>Operating temperature</b></td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td><b>Operating relative humidity</b></td> <td>5% to 90%, noncondensing</td> </tr> <tr> <td><b>Nonoperating/Storage temperature</b></td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td><b>Nonoperating/Storage relative humidity</b></td> <td>5% to 90%, noncondensing</td> </tr> </table>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)	<b>Operating relative humidity</b>	5% to 90%, noncondensing	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing		
<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)										
<b>Operating relative humidity</b>	5% to 90%, noncondensing										
<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)										
<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing										
<b>Electrical characteristics</b>	<table border="0"> <tr> <td><b>Maximum heat dissipation</b></td> <td>85 BTU/hr (89.68 kJ/hr)</td> </tr> <tr> <td><b>Voltage</b></td> <td>100-120/200-240 VAC</td> </tr> <tr> <td><b>Maximum power rating</b></td> <td>25 W</td> </tr> <tr> <td><b>Frequency</b></td> <td>50/60 Hz</td> </tr> <tr> <td><b>Notes</b></td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> </table>	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)	<b>Voltage</b>	100-120/200-240 VAC	<b>Maximum power rating</b>	25 W	<b>Frequency</b>	50/60 Hz	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)										
<b>Voltage</b>	100-120/200-240 VAC										
<b>Maximum power rating</b>	25 W										
<b>Frequency</b>	50/60 Hz										
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.										
<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1										

### Technical Specifications

AS/NZS 60950  
EN 60825-1 Safety of Laser Products-Part 1  
EN 60825-2 Safety of Laser Products-Part 2  
IEC 60950-1  
EN 60950-1  
CAN/CSA-C22.2 No. 60950-1-03  
EN 60950-1/A11  
FDA 21 CFR Subchapter J

#### Emissions

EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B

#### Telecom

FCC part 68; CS-03

#### Management

IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB

#### Notes

The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.

#### Services

3-year, parts only, global next-day advance exchange (UW075E)  
3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)  
3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)  
3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)  
3-year, 24x7 SW phone support, software updates (UW012E)  
1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)  
1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)  
1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)  
4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)  
4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)  
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)  
4-year, 24x7 SW phone support, software updates (UW013E)  
5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)  
5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)  
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)  
5-year, 24x7 SW phone support, software updates (UW014E)  
3 Yr 6 hr Call-to-Repair Onsite (UW079E)  
4 Yr 6 hr Call-to-Repair Onsite (UW080E)  
5 Yr 6 hr Call-to-Repair Onsite (UW081E)  
1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)  
1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

#### HP MSR20-12-T Router (JF806A)

**Ports** 1 SIC slot

### Technical Specifications

1 T1 port  
 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full  
 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full

<b>Physical characteristics</b>	<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	<b>Weight</b>	6.61 lb (3 kg)
<b>Memory and processor</b>	<b>Processor</b>	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
<b>Performance</b>	<b>Throughput</b>	up to 160 Kpps (64-byte packets)
	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	5% to 90%, noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)
	<b>Voltage</b>	100-120/200-240 VAC
	<b>Maximum power rating</b>	25 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B	
<b>Telecom</b>	FCC part 68; CS-03	

### Technical Specifications

<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (UW075E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)</p> <p>3-year, 24x7 SW phone support, software updates (UW012E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)</p> <p>4-year, 24x7 SW phone support, software updates (UW013E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)</p> <p>5-year, 24x7 SW phone support, software updates (UW014E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW079E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW080E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW081E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)</p> <p>1-year, 24x7 software phone support, software updates (HR557E)</p>
	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

#### HP MSR20-12-T-W Router (NA) (JG209A)

<b>Ports</b>	1 SIC slot
	1 T1 port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>AP characteristics</b>	<b>Radios</b> Single (b/g)
	<b>Radio operation modes</b> Client access
	<b>AP operation modes</b> Autonomous
	<b>Wi-Fi Alliance Certification*</b> b/g Wi-Fi Certified

### Technical Specifications

\* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

<b>Physical characteristics</b>	<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	<b>Weight</b>	6.79 lb (3.08 kg)
<b>Memory and processor</b>	<b>Processor</b>	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
<b>Performance</b>	<b>Throughput</b>	up to 160 Kpps (64-byte packets)
	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	5% to 90%, noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
<b>Electrical characteristics</b>	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing
	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)
	<b>Voltage</b>	100-120/200-240 VAC
	<b>Maximum power rating</b>	25 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B	
<b>Telecom</b>	FCC part 68; CS-03	
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	

### Technical Specifications

<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (UW075E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)</p> <p>3-year, 24x7 SW phone support, software updates (UW012E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)</p> <p>4-year, 24x7 SW phone support, software updates (UW013E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)</p> <p>5-year, 24x7 SW phone support, software updates (UW014E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW079E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW080E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW081E)</p>

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### HP MSR20-13 Router (JF240A)

<b>Ports</b>	<p>1 SIC slot</p> <p>1 RJ-11 4-wire G.shdsl port</p> <p>1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p> <p>4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p>
<b>Physical characteristics</b>	<p><b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</p> <p><b>Weight</b> 6.61 lb (3.0 kg)</p>
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<p><b>Throughput</b> up to 160 Kpps (64-byte packets)</p> <p><b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)</p>
<b>Environment</b>	<p><b>Operating temperature</b> 32°F to 104°F (0°C to 40°C)</p> <p><b>Operating relative humidity</b> 5%% to 90%%, noncondensing</p> <p><b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)</p>

### Technical Specifications

	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)
	<b>Voltage</b>	100-120/200-240 VAC
	<b>Maximum power rating</b>	25 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B	
<b>Telecom</b>	FCC part 68; CS-03	
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.	
<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)	

### Technical Specifications

5-year, 24x7 SW phone support, software updates (UW014E)  
 3 Yr 6 hr Call-to-Repair Onsite (UW079E)  
 4 Yr 6 hr Call-to-Repair Onsite (UW080E)  
 5 Yr 6 hr Call-to-Repair Onsite (UW081E)  
 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)  
 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-13-W Router (JF808A)

<b>Ports</b>	1 SIC slot 1 RJ-11 4-wire G.shdsl port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full								
<b>AP characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Radios</b></td> <td>Single (b/g)</td> </tr> <tr> <td style="vertical-align: top;"><b>Radio operation modes</b></td> <td>Client access</td> </tr> <tr> <td style="vertical-align: top;"><b>AP operation modes</b></td> <td>Autonomous</td> </tr> <tr> <td style="vertical-align: top;"><b>Wi-Fi Alliance Certification*</b></td> <td>b/g Wi-Fi Certified</td> </tr> </table> <p>* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing preformed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.</p>	<b>Radios</b>	Single (b/g)	<b>Radio operation modes</b>	Client access	<b>AP operation modes</b>	Autonomous	<b>Wi-Fi Alliance Certification*</b>	b/g Wi-Fi Certified
<b>Radios</b>	Single (b/g)								
<b>Radio operation modes</b>	Client access								
<b>AP operation modes</b>	Autonomous								
<b>Wi-Fi Alliance Certification*</b>	b/g Wi-Fi Certified								
<b>Physical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Dimensions</b></td> <td>11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;"><b>Weight</b></td> <td>6.61 lb (3.0 kg)</td> </tr> </table>	<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)	<b>Weight</b>	6.61 lb (3.0 kg)				
<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)								
<b>Weight</b>	6.61 lb (3.0 kg)								
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash								
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.								
<b>Performance</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Throughput</b></td> <td>up to 160 Kpps (64-byte packets)</td> </tr> <tr> <td style="vertical-align: top;"><b>Routing table size</b></td> <td>10000 entries (IPv4), 10000 entries (IPv6)</td> </tr> </table>	<b>Throughput</b>	up to 160 Kpps (64-byte packets)	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)				
<b>Throughput</b>	up to 160 Kpps (64-byte packets)								
<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)								
<b>Environment</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Operating temperature</b></td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Operating relative humidity</b></td> <td>5% to 95%, noncondensing</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage temperature</b></td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage relative humidity</b></td> <td>5% to 95%, noncondensing</td> </tr> </table>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)	<b>Operating relative humidity</b>	5% to 95%, noncondensing	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)	<b>Nonoperating/Storage relative humidity</b>	5% to 95%, noncondensing
<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)								
<b>Operating relative humidity</b>	5% to 95%, noncondensing								
<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)								
<b>Nonoperating/Storage relative humidity</b>	5% to 95%, noncondensing								
<b>Electrical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Maximum heat dissipation</b></td> <td>85 BTU/hr (89.68 kJ/hr)</td> </tr> <tr> <td style="vertical-align: top;"><b>Voltage</b></td> <td>100-120/200-240 VAC</td> </tr> <tr> <td style="vertical-align: top;"><b>Maximum power rating</b></td> <td>25 W</td> </tr> </table>	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)	<b>Voltage</b>	100-120/200-240 VAC	<b>Maximum power rating</b>	25 W		
<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)								
<b>Voltage</b>	100-120/200-240 VAC								
<b>Maximum power rating</b>	25 W								

### Technical Specifications

<b>Frequency</b>	50/60 Hz
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

<b>Safety</b>	<p>UL 60950-1            CAN/CSA 22.2 No. 60950-1            AS/NZS 60950            EN 60825-1 Safety of Laser Products-Part 1            EN 60825-2 Safety of Laser Products-Part 2            IEC 60950-1            EN 60950-1            CAN/CSA-C22.2 No. 60950-1-03            EN 60950-1/A11            FDA 21 CFR Subchapter J</p>
<b>Emissions</b>	<p>EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B</p>
<b>Telecom</b>	FCC part 68; CS-03
<b>Management</b>	<p>IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (Serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB</p>
<b>Notes</b>	<p>The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.</p>
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (UW075E)            3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)            3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)            3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)            3-year, 24x7 SW phone support, software updates (UW012E)            1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)            1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)            1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)            4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)            4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)            4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)            4-year, 24x7 SW phone support, software updates (UW013E)            5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)            5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)            5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)            5-year, 24x7 SW phone support, software updates (UW014E)            3 Yr 6 hr Call-to-Repair Onsite (UW079E)            4 Yr 6 hr Call-to-Repair Onsite (UW080E)            5 Yr 6 hr Call-to-Repair Onsite (UW081E)            1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)            1-year, 24x7 software phone support, software updates (HR557E)</p>

### Technical Specifications

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-13-W Router (NA) (JG210A)

<b>Ports</b>	1 SIC slot 1 T1 port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full										
<b>AP characteristics</b>	<table border="0"> <tr> <td><b>Radios</b></td> <td>Single (b/g)</td> </tr> <tr> <td><b>Radio operation modes</b></td> <td>Client access</td> </tr> <tr> <td><b>AP operation modes</b></td> <td>Autonomous</td> </tr> <tr> <td><b>Wi-Fi Alliance Certification*</b></td> <td>b/g Wi-Fi Certified</td> </tr> </table> <p>* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing preformed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.</p>	<b>Radios</b>	Single (b/g)	<b>Radio operation modes</b>	Client access	<b>AP operation modes</b>	Autonomous	<b>Wi-Fi Alliance Certification*</b>	b/g Wi-Fi Certified		
<b>Radios</b>	Single (b/g)										
<b>Radio operation modes</b>	Client access										
<b>AP operation modes</b>	Autonomous										
<b>Wi-Fi Alliance Certification*</b>	b/g Wi-Fi Certified										
<b>Physical characteristics</b>	<table border="0"> <tr> <td><b>Dimensions</b></td> <td>11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</td> </tr> <tr> <td><b>Weight</b></td> <td>7.01 lb (3.18 kg)</td> </tr> </table>	<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)	<b>Weight</b>	7.01 lb (3.18 kg)						
<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)										
<b>Weight</b>	7.01 lb (3.18 kg)										
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash										
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.										
<b>Performance</b>	<table border="0"> <tr> <td><b>Throughput</b></td> <td>up to 160 Kpps (64-byte packets)</td> </tr> <tr> <td><b>Routing table size</b></td> <td>10000 entries (IPv4), 10000 entries (IPv6)</td> </tr> </table>	<b>Throughput</b>	up to 160 Kpps (64-byte packets)	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)						
<b>Throughput</b>	up to 160 Kpps (64-byte packets)										
<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)										
<b>Environment</b>	<table border="0"> <tr> <td><b>Operating temperature</b></td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td><b>Operating relative humidity</b></td> <td>5% to 95%, noncondensing</td> </tr> <tr> <td><b>Nonoperating/Storage temperature</b></td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td><b>Nonoperating/Storage relative humidity</b></td> <td>5% to 95%, noncondensing</td> </tr> </table>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)	<b>Operating relative humidity</b>	5% to 95%, noncondensing	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)	<b>Nonoperating/Storage relative humidity</b>	5% to 95%, noncondensing		
<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)										
<b>Operating relative humidity</b>	5% to 95%, noncondensing										
<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)										
<b>Nonoperating/Storage relative humidity</b>	5% to 95%, noncondensing										
<b>Electrical characteristics</b>	<table border="0"> <tr> <td><b>Maximum heat dissipation</b></td> <td>85 BTU/hr (89.68 kJ/hr)</td> </tr> <tr> <td><b>Voltage</b></td> <td>100-120/200-240 VAC</td> </tr> <tr> <td><b>Maximum power rating</b></td> <td>25 W</td> </tr> <tr> <td><b>Frequency</b></td> <td>50/60 Hz</td> </tr> <tr> <td><b>Notes</b></td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> </table>	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)	<b>Voltage</b>	100-120/200-240 VAC	<b>Maximum power rating</b>	25 W	<b>Frequency</b>	50/60 Hz	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)										
<b>Voltage</b>	100-120/200-240 VAC										
<b>Maximum power rating</b>	25 W										
<b>Frequency</b>	50/60 Hz										
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.										
<b>Safety</b>	UL 60950-1										

### Technical Specifications

CAN/CSA 22.2 No. 60950-1  
AS/NZS 60950  
EN 60825-1 Safety of Laser Products-Part 1  
EN 60825-2 Safety of Laser Products-Part 2  
IEC 60950-1  
EN 60950-1  
CAN/CSA-C22.2 No. 60950-1-03  
EN 60950-1/A11  
FDA 21 CFR Subchapter J

#### Emissions

EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B

#### Telecom

FCC part 68; CS-03

#### Management

IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB

#### Notes

The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.

#### Services

3-year, parts only, global next-day advance exchange (UW075E)  
3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)  
3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)  
3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)  
3-year, 24x7 SW phone support, software updates (UW012E)  
4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)  
4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)  
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)  
4-year, 24x7 SW phone support, software updates (UW013E)  
5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)  
5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)  
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)  
5-year, 24x7 SW phone support, software updates (UW014E)  
3 Yr 6 hr Call-to-Repair Onsite (UW079E)  
4 Yr 6 hr Call-to-Repair Onsite (UW080E)  
5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

### HP MSR20-15-A Router (JF237A)

#### Ports

1 SIC slot  
1 RJ-45 ADSL2+ port  
1 Analog Modem port  
1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX);  
Duplex: half or full

### Technical Specifications

	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<p><b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</p> <p><b>Weight</b> 6.61 lb (3.0 kg)</p>
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<p><b>Throughput</b> up to 160 Kpps (64-byte packets)</p> <p><b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)</p>
<b>Environment</b>	<p><b>Operating temperature</b> 32°F to 104°F (0°C to 40°C)</p> <p><b>Operating relative humidity</b> 5% to 90%, noncondensing</p> <p><b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)</p> <p><b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing</p>
<b>Electrical characteristics</b>	<p><b>Maximum heat dissipation</b> 85 BTU/hr (89.68 kJ/hr)</p> <p><b>Voltage</b> 100-120/200-240 VAC</p> <p><b>Maximum power rating</b> 25 W</p> <p><b>Frequency</b> 50/60 Hz</p> <p><b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>
<b>Safety</b>	<p>UL 60950-1</p> <p>CAN/CSA 22.2 No. 60950-1</p> <p>AS/NZS 60950</p> <p>EN 60825-1 Safety of Laser Products-Part 1</p> <p>EN 60825-2 Safety of Laser Products-Part 2</p> <p>IEC 60950-1</p> <p>EN 60950-1</p> <p>CAN/CSA-C22.2 No. 60950-1-03</p> <p>EN 60950-1/A11</p> <p>FDA 21 CFR Subchapter J</p>
<b>Emissions</b>	<p>EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B</p>
<b>Telecom</b>	FCC part 68; CS-03
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.

### Technical Specifications

<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E)
	3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)
	3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)
	3-year, 24x7 SW phone support, software updates (UW012E)
	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)
	4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
	4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
	5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
	5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
	5-year, 24x7 SW phone support, software updates (UW014E)
	3 Yr 6 hr Call-to-Repair Onsite (UW079E)
	4 Yr 6 hr Call-to-Repair Onsite (UW080E)
5 Yr 6 hr Call-to-Repair Onsite (UW081E)	
1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)	
1-year, 24x7 software phone support, software updates (HR557E)	

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-15-A-W Router (JF809A)

<b>Ports</b>	1 SIC slot
	1 RJ-45 ADSL2+ port
	1 Analog Modem port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full

<b>AP characteristics</b>	<b>Radios</b>	Single (b/g)
	<b>Radio operation modes</b>	Client access
	<b>AP operation modes</b>	Autonomous
	<b>Wi-Fi Alliance Certification*</b>	b/g Wi-Fi Certified

\* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

<b>Physical characteristics</b>	<b>Dimensions</b>	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	<b>Weight</b>	6.61 lb (3.0 kg)
<b>Memory and processor</b>	<b>Processor</b>	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	

### Technical Specifications

<b>Performance</b>	<b>Throughput</b>	up to 160 Kpps (64-byte packets)
	<b>Routing table size</b>	10000 entries (IPv4), 10000 entries (IPv6)
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	5% to 90%, noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	85 BTU/hr (89.68 kJ/hr)
	<b>Voltage</b>	100-120/200-240 VAC
	<b>Maximum power rating</b>	25 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>		UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
<b>Emissions</b>		EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B
<b>Telecom</b>		FCC part 68; CS-03
<b>Management</b>		IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>		The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.
<b>Services</b>		3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)

### Technical Specifications

- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-15-I Router (JF236A)

<b>Ports</b>	<ul style="list-style-type: none"> <li>1 SIC slot</li> <li>1 RJ-45 ADSL2+ port</li> <li>1 ISDN port</li> <li>1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</li> <li>4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</li> </ul>
<b>Physical characteristics</b>	<ul style="list-style-type: none"> <li><b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</li> <li><b>Weight</b> 6.61 lb (3.0 kg)</li> </ul>
<b>Memory and processor</b>	<ul style="list-style-type: none"> <li><b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash</li> </ul>
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<ul style="list-style-type: none"> <li><b>Throughput</b> up to 160 Kpps (64-byte packets)</li> <li><b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)</li> </ul>
<b>Environment</b>	<ul style="list-style-type: none"> <li><b>Operating temperature</b> 32°F to 104°F (0°C to 40°C)</li> <li><b>Operating relative humidity</b> 5% to 90%, noncondensing</li> <li><b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)</li> <li><b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing</li> </ul>
<b>Electrical characteristics</b>	<ul style="list-style-type: none"> <li><b>Maximum heat dissipation</b> 85 BTU/hr (89.68 kJ/hr)</li> <li><b>Voltage</b> 100-120/200-240 VAC</li> </ul>

### Technical Specifications

<b>Maximum power rating</b>	25 W
<b>Frequency</b>	50/60 Hz
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

<b>Safety</b>	<p>UL 60950-1            CAN/CSA 22.2 No. 60950-1            AS/NZS 60950            EN 60825-1 Safety of Laser Products-Part 1            EN 60825-2 Safety of Laser Products-Part 2            IEC 60950-1            EN 60950-1            CAN/CSA-C22.2 No. 60950-1-03            EN 60950-1/A11            FDA 21 CFR Subchapter J</p>
<b>Emissions</b>	<p>EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B</p>
<b>Telecom</b>	FCC part 68; CS-03
<b>Management</b>	<p>IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB</p>
<b>Notes</b>	<p>The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.</p>
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (UW075E)            3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)            3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)            3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)            3-year, 24x7 SW phone support, software updates (UW012E)            1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)            1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)            1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)            4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)            4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)            4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)            4-year, 24x7 SW phone support, software updates (UW013E)            5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)            5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)            5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)            5-year, 24x7 SW phone support, software updates (UW014E)            3 Yr 6 hr Call-to-Repair Onsite (UW079E)            4 Yr 6 hr Call-to-Repair Onsite (UW080E)            5 Yr 6 hr Call-to-Repair Onsite (UW081E)            1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)            1-year, 24x7 software phone support, software updates (HR557E)</p>

### Technical Specifications

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-15-I-W Router (JF238A)

<b>Ports</b>	<ul style="list-style-type: none"> <li>1 SIC slot</li> <li>1 RJ-45 ADSL2+ port</li> <li>1 ISDN port</li> <li>1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</li> <li>4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</li> </ul>
<b>AP characteristics</b>	<ul style="list-style-type: none"> <li><b>Radios</b> Single (b/g)</li> <li><b>Radio operation modes</b> Client access</li> <li><b>AP operation modes</b> Autonomous</li> <li><b>Wi-Fi Alliance Certification*</b> b/g Wi-Fi Certified</li> </ul> <p>* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.</p>
<b>Physical characteristics</b>	<ul style="list-style-type: none"> <li><b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</li> <li><b>Weight</b> 6.61 lb (3 kg)</li> </ul>
<b>Memory and processor</b>	<ul style="list-style-type: none"> <li><b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash</li> </ul>
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<ul style="list-style-type: none"> <li><b>Throughput</b> up to 160 Kpps (64-byte packets)</li> <li><b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)</li> </ul>
<b>Environment</b>	<ul style="list-style-type: none"> <li><b>Operating temperature</b> 32°F to 104°F (0°C to 40°C)</li> <li><b>Operating relative humidity</b> 5% to 90%, noncondensing</li> <li><b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)</li> <li><b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing</li> </ul>
<b>Electrical characteristics</b>	<ul style="list-style-type: none"> <li><b>Maximum heat dissipation</b> 85 BTU/hr (89.68 kJ/hr)</li> <li><b>Voltage</b> 100-120/200-240 VAC</li> <li><b>Maximum power rating</b> 25 W</li> <li><b>Frequency</b> 50/60 Hz</li> </ul>

### Technical Specifications

**Notes** Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B
<b>Telecom</b>	FCC part 68; CS-03
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed.
<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E) 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions

### Technical Specifications

and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP MSR20-15 Router (JF817A)

<b>Ports</b>	1 SIC slot 1 RJ-45 ADSL2+ port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
<b>Physical characteristics</b>	<b>Dimensions</b> 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height) <b>Weight</b> 6.61 lb (3.0 kg)
<b>Memory and processor</b>	<b>Processor</b> RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
<b>Mounting</b>	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
<b>Performance</b>	<b>Throughput</b> up to 160 Kpps (64-byte packets) <b>Routing table size</b> 10000 entries (IPv4), 10000 entries (IPv6)
<b>Environment</b>	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C) <b>Operating relative humidity</b> 5% to 90%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 5% to 90%, noncondensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b> 85 BTU/hr (89.68 kJ/hr) <b>Voltage</b> 100-120/200-240 VAC <b>Maximum power rating</b> 25 W <b>Frequency</b> 50/60 Hz <b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J

### Technical Specifications

<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR 22 Class B; FCC (CFR 47, Part 15) Class B
<b>Telecom</b>	FCC part 68; CS-03
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models; weight is with no optional modules installed. The JF817A is for the Brazilian market only. If other regions have similar requirements, other options are the JF236A, JF809A, JF237A, and JF238A.
<b>Services</b>	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E) 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Standards and protocols (applies to all products in series)

<b>BGP</b>	RFC 3214 LSP Modification Using CR-LDP
RFC 1163 Border Gateway Protocol (BGP)	RFC 3215 LDP State Machine
RFC 1267 Border Gateway Protocol 3 (BGP-3)	RFC 3268 Advanced Encryption Standard (AES)
RFC 1657 Definitions of Managed Objects for BGPv4	Ciphersuites for Transport Layer Security (TLS)
RFC 1771 BGPv4	RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 1772 Application of the BGP	RFC 3279 Algorithms and Identifiers for the Internet
RFC 1773 Experience with the BGP-4 Protocol	X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1774 BGP-4 Protocol Analysis	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1965 BGP4 confederations	Profile
RFC 1997 BGP Communities Attribute	RFC 3392 Support BGP capabilities advertisement
RFC 1998 PPP Gandalf FZA Compression Protocol	

### Technical Specifications

RFC 2385 BGP Session Protection via TCP MD5  
RFC 2439 BGP Route Flap Damping

#### Device management

RFC 1305 NTPv3  
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0  
RFC 2271 FrameWork  
RFC 2452 MIB for TCP6  
RFC 2454 MIB for UDP6

#### General protocols

IEEE 802.1D MAC Bridges  
IEEE 802.1p Priority  
IEEE 802.1Q VLANs  
IEEE 802.1s Multiple Spanning Trees  
IEEE 802.1w Rapid Reconfiguration of Spanning Tree  
RFC 768 UDP  
RFC 783 TFTP Protocol (revision 2)  
RFC 791 IP  
RFC 792 ICMP  
RFC 793 TCP  
RFC 826 ARP  
RFC 854 TELNET  
RFC 855 Telnet Option Specification  
RFC 856 TELNET  
RFC 858 Telnet Suppress Go Ahead Option  
RFC 894 IP over Ethernet  
RFC 925 Multi-LAN Address Resolution  
RFC 950 Internet Standard Subnetting Procedure  
RFC 959 File Transfer Protocol (FTP)  
RFC 1006 ISO transport services on top of the TCP: Version 3  
RFC 1027 Proxy ARP  
RFC 1034 Domain Concepts and Facilities  
RFC 1035 Domain Implementation and Specification  
RFC 1042 IP Datagrams  
RFC 1058 RIPv1  
RFC 1071 Computing the Internet Checksum  
RFC 1091 Telnet Terminal-Type Option  
RFC 1122 Host Requirements  
RFC 1141 Incremental updating of the Internet checksum  
RFC 1142 OSI IS-IS Intra-domain Routing Protocol  
RFC 1144 Compressing TCP/IP headers for low-speed serial links  
RFC 1195 OSI ISIS for IP and Dual Environments  
RFC 1256 ICMP Router Discovery Protocol (IRDP)  
RFC 1293 Inverse Address Resolution Protocol  
RFC 1315 Management Information Base for Frame Relay DTEs  
RFC 1332 The PPP Internet Protocol Control

RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)  
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering  
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec  
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers  
RFC 3784 ISIS TE support  
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit  
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management  
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)  
RFC 3847 Restart signaling for IS-IS  
FRF.1.2 PVC User-to-Network Interface (UNI) Implementation Agreement - July 2000  
FRF.11.1 Voice over Frame Relay Implementation Agreement - May 1997 - Annex J added March 1999  
FRF.12 Frame Relay Fragmentation Implementation Agreement - December 1997  
FRF.16.1 Multilink Frame Relay UNI/NNI Implementation Agreement - May 2002  
FRF.2.2 Frame Relay Network-to-Network Interface (NNI) Implementation Agreement - March 2002  
FRF.20 Frame Relay IP Header Compression Implementation Agreement - June 2001  
FRF.3.2 Frame Relay Multiprotocol Encapsulation Implementation Agreement - April 2000  
FRF.7 Frame Relay PVC Multicast Service and Protocol Description - October 1994  
FRF.9 Data Compression Over Frame Relay Implementation Agreement - January 1996

#### IP multicast

RFC 1112 IGMP  
RFC 2236 IGMPv2  
RFC 2283 Multiprotocol Extensions for BGP-4  
RFC 2362 PIM Sparse Mode  
RFC 2365 Administratively Scoped IP Multicast  
RFC 2710 Multicast Listener Discovery (MLD) for IPv6  
RFC 2934 Protocol Independent Multicast MIB for IPv4  
RFC 3376 IGMPv3

#### IPv6

### Technical Specifications

Protocol (IPCP)	RFC 1981 IPv6 Path MTU Discovery
RFC 1333 PPP Link Quality Monitoring	RFC 2080 RIPng for IPv6
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2292 Advanced Sockets API for IPv6
RFC 1349 Type of Service	RFC 2373 IPv6 Addressing Architecture
RFC 1350 TFTP Protocol (revision 2)	RFC 2460 IPv6 Specification
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2463 ICMPv6
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2472 IP Version 6 over PPP
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 2475 IPv6 DiffServ Architecture
RFC 1519 CIDR	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1534 DHCP/BOOTP Interoperation	RFC 2545 Use of MP-BGP-4 for IPv6
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)	RFC 2740 OSPFv3 for IPv6
RFC 1577 Classical IP and ARP over ATM	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 1624 Incremental Internet Checksum	RFC 3513 IPv6 Addressing Architecture
RFC 1631 NAT	RFC 3596 DNS Extension for IPv6
RFC 1638 PPP Bridging Control Protocol (BCP)	<b>MIBs</b>
RFC 1661 The Point-to-Point Protocol (PPP)	RFC 1213 MIB II
RFC 1662 PPP in HDLC-like Framing	RFC 1229 Interface MIB Extensions
RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2	RFC 1286 Bridge MIB
RFC 1701 Generic Routing Encapsulation	RFC 1493 Bridge MIB
RFC 1702 Generic Routing Encapsulation over IPv4 networks	RFC 1573 SNMP MIB II
RFC 1721 RIP-2 Analysis	RFC 1724 RIPv2 MIB
RFC 1722 RIP-2 Applicability	RFC 1757 Remote Network Monitoring MIB
RFC 1723 RIP v2	RFC 1850 OSPFv2 MIB
RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1	RFC 2011 SNMPv2 MIB for IP
RFC 1812 IPv4 Routing	RFC 2012 SNMPv2 MIB for TCP
RFC 1829 The ESP DES-CBC Transform	RFC 2013 SNMPv2 MIB for UDP
RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses	RFC 2233 Interfaces MIB
RFC 1944 Benchmarking Methodology for Network Interconnect Devices	RFC 2454 IPV6-UDP-MIB
RFC 1973 PPP in Frame Relay	RFC 2465 IPv6 MIB
RFC 1974 PPP Stac LZS Compression Protocol	RFC 2466 ICMPv6 MIB
RFC 1990 The PPP Multilink Protocol (MP)	RFC 2618 RADIUS Client MIB
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)	RFC 2620 RADIUS Accounting MIB
RFC 2091 Trigger RIP	RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2131 DHCP	RFC 2737 Entity MIB (Version 2)
	RFC 2863 The Interfaces Group MIB
	RFC 2933 IGMP MIB
	RFC 3813 MPLS LSR MIB
	<b>Network management</b>
	IEEE 802.1D (STP)
	RFC 1155 Structure of Management Information
	RFC 1157 SNMPv1

### Technical Specifications

- RFC 2132 DHCP Options and BOOTP Vendor Extensions
  - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLsw v2.0 Enhancements
  - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
  - RFC 2280 Routing Policy Specification Language (RPSL)
  - RFC 2284 EAP over LAN
  - RFC 2338 VRRP
  - RFC 2364 PPP Over AAL5
  - RFC 2374 An Aggregatable Global Unicast Address Format
  - RFC 2451 The ESP CBC-Mode Cipher Algorithms
  - RFC 2453 RIPv2
  - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
  - RFC 2511 Internet X.509 Certificate Request Message Format
  - RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
  - RFC 2644 Directed Broadcast Control
  - RFC 2661 L2TP
  - RFC 2663 NAT Terminology and Considerations
  - RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
  - RFC 2694 DNS extensions to Network Address Translators (DNS\_ALG)
  - RFC 2702 Requirements for Traffic Engineering Over MPLS
  - RFC 2747 RSVP Cryptographic Authentication
  - RFC 2763 Dynamic Name-to-System ID mapping support
  - RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
  - RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
  - RFC 2784 Generic Routing Encapsulation (GRE)
  - RFC 2787 Definitions of Managed Objects for VRRP
  - RFC 2961 RSVP Refresh Overhead Reduction Extensions
  - RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
  - RFC 2973 IS-IS Mesh Groups
  - RFC 2993 Architectural Implications of NAT
  - RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
  - RFC 3027 Protocol Complications with the IP Network Address Translator
  - RFC 3031 Multiprotocol Label Switching Architecture
  - RFC 3032 MPLS Label Stack Encoding
  - RFC 2272 SNMPv3 Management Protocol
  - RFC 2273 SNMPv3 Applications
  - RFC 2274 USM for SNMPv3
  - RFC 2275 VACM for SNMPv3
  - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
  - RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
  - RFC 1246 Experience with OSPF
  - RFC 1587 OSPF NSSA
  - RFC 1765 OSPF Database Overflow
  - RFC 1850 OSPFv2 Management Information Base (MIB), traps
  - RFC 2328 OSPFv2
  - RFC 2370 OSPF Opaque LSA Option
  - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
  - RFC 2474 DS Field in the IPv4 and IPv6 Headers
  - RFC 2475 DiffServ Architecture
  - RFC 2597 DiffServ Assured Forwarding (AF)
  - RFC 2598 DiffServ Expedited Forwarding (EF)
  - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
  - RFC 1321 The MD5 Message-Digest Algorithm
  - RFC 2082 RIP-2 MD5 Authentication
  - RFC 2104 Keyed-Hashing for Message Authentication
  - RFC 2138 RADIUS Authentication
  - RFC 2209 RSVP-Message Processing
  - RFC 2246 Transport Layer Security (TLS)
  - RFC 2716 PPP EAP TLS Authentication Protocol
  - RFC 2865 RADIUS Authentication
  - RFC 2866 RADIUS Accounting
  - RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
- VPN**
- RFC 2403 - HMAC-MD5-96
  - RFC 2404 - HMAC-SHA1-96
  - RFC 2405 - DES-CBC Cipher algorithm
  - RFC 2547 BGP/MPLS VPNs
  - RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP

### Technical Specifications

RFC 3036 LDP Specification  
RFC 3046 DHCP Relay Agent Information Option  
RFC 3063 MPLS Loop Prevention Mechanism  
RFC 3065 Support AS confederation  
RFC 3137 OSPF Stub Router Advertisement  
RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels  
RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels  
RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)

RFC 3270 TE Capabilities Advertisement with BGP  
RFC 2858 Multiprotocol Extensions for BGP-4  
RFC 2918 Route Refresh Capability for BGP-4  
RFC 3107 Carrying Label Information in BGP-4

#### **IPsec**

RFC 1828 IP Authentication using Keyed MD5  
RFC 2401 IP Security Architecture  
RFC 2402 IP Authentication Header  
RFC 2406 IP Encapsulating Security Payload  
RFC 2407 - Domain of interpretation  
RFC 2410 - The NULL Encryption Algorithm and its use with IPsec  
RFC 2411 IP Security Document Roadmap  
RFC 2412 – OAKLEY  
RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

### Accessories

#### HP MSR20-1x Series accessories

#### Transceivers

HP X110 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
<a href="#">HP X120 1G SFP LC SX Transceiver</a>	JD118B
<a href="#">HP X120 1G SFP LC LX Transceiver</a>	JD119B
<a href="#">HP X125 1G SFP LC LH40 1310nm Transceiver</a>	JD061A
<a href="#">HP X120 1G SFP LC LH40 1550nm Transceiver</a>	JD062A
<a href="#">HP X125 1G SFP LC LH70 Transceiver</a>	JD063B
HP X120 1G SFP LC LH100 Transceiver	JD103A
<a href="#">HP X120 1G SFP LC BX 10-U Transceiver</a>	JD098B
<a href="#">HP X120 1G SFP LC BX 10-D Transceiver</a>	JD099B

#### Cables

HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A
HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A
HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 BNC 75 ohm 3m Router Cable	JD175A
HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Voice Router Cable	JD535A
HP X260 T1 Router Cable	JD518A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 T1VI DB15M RJ45 3m Router Cable	JF843A
HP X260 mini D-28 to 4-RJ45 0.3m Router Cable	JG263A

#### Mounting Kit

HP 3100/4210-16/-8 PoE Rack Mount Kit	JD323A
---------------------------------------	--------

#### Router Modules

### Accessories

HP MSR 9-port 10/100Base-T Switch DSIC Module	JD574B
HP MSR 4-port 10/100Base-T Switch SIC Module	JD573B
HP MSR 1-port GbE Combo SIC Module	JD572A
HP MSR 1-port 10/100Base-T SIC Module	JD545B
HP MSR 1-port 100Base-X SIC Module	JF280A
HP MSR 2-port FXO SIC Module	JD558A
HP MSR 1-port FXO SIC Module	JD559A
HP MSR 2-port FXS SIC Module	JD560A
HP MSR 1-port FXS SIC Module	JD561A
HP MSR 2-port FXS/1-port FXO SIC Module	JD632A
HP MSR 2-port ISDN-S/T Voice SIC Module	JF821A
HP MSR 1-port ADSL2+ SIC Module	JD537A
<a href="#">HP MSR 1-port ADSL over ISDN SIC Module</a>	JG056B
HP MSR 1-port 8-wire G.SHDSL (RJ45) DSIC Module	JG191A
HP MSR 1-port E1/Fractional E1 (75ohm) SIC Module	JD634B
HP MSR 2-port E1/Fractional E1 (75ohm) SIC Module	JF842A
HP MSR 1-port T1/Fractional T1 SIC Module	JD538A
HP MSR 1-port Enhanced Sync/Async Serial SIC Module	JD557A
HP MSR 1-port ISDN-S/T SIC Module	JD571A
HP MSR 16-port Async Serial SIC Module	JG186A
<a href="#">HP MSR 8-port Async Serial SIC Module</a>	JF281A
HP MSR 802.11b/g/n Wireless Access Point SIC Module	JF819A
HP MSR 802.11b/g/n Wireless Access Point SIC Module (NA)	JG211A
HP MSR 1-port E1/CE1/PRI SIC Module	JF253B
HP MSR 4-port FXS / 1-port FXO DSIC Module	JG189A
HP MSR HSPA/WCDMA SIC Module	JG187A
<b>HP MSR20-12 Router (JF241A)</b>	
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
<b>HP MSR20-12-W Router (JF807A)</b>	
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A

### Accessories

HP MSR Voice Co-processor Module	JD610A
<b>HP MSR20-12-T Router (JF806A)</b>	
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
<b>HP MSR20-12-T-W Router (NA) (JG209A)</b>	
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
<b>HP MSR20-15-A Router (JF237A)</b>	
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
<b>HP MSR20-15-A-W Router (JF809A)</b>	
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
<b>HP MSR20-15-I Router (JF236A)</b>	
HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

### Accessories

#### **HP MSR20-15-I-W Router (JF238A)**

HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

#### **HP MSR20-15 Router (JF817A)**

HP MSR 1-port E1 Voice SIC Module	JD575A
HP MSR 1-port T1 Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

### Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

<b>HP X120 1G SFP LC SX Transceiver (JD118B)</b>  A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.	<b>Ports</b>	1 LC 1000BASE-SX port	
	<b>Connectivity</b>	<b>Connector type</b>	LC
	<b>Physical characteristics</b>	<b>Wavelength</b>	850 nm
		<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		<b>Full configuration weight</b>	0.04 lb. (0.02 kg)
	<b>Electrical characteristics</b>	<b>Power consumption typical</b>	0.8 W
		<b>Power consumption maximum</b>	1.0 W
	<b>Cabling</b>	Maximum distance:	
		• FDDI Grade distance = 220m	
		• OM1 = 275m	
	• OM2 = 500m		
	• OM3 = Not Specified by standard		
	Cable length	up to 550m	
	Fiber type	Multi Mode	
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

<b>HP X120 1G SFP LC LX Transceiver (JD119B)</b>  A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF	<b>Ports</b>	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)	
	<b>Connectivity</b>	<b>Connector type</b>	LC
	<b>Physical characteristics</b>	<b>Wavelength</b>	1300 nm
		<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		<b>Full configuration weight</b>	0.04 lb. (0.02 kg)
	<b>Electrical characteristics</b>	<b>Power consumption typical</b>	0.8 W
		<b>Power consumption maximum</b>	1.0 W
	<b>Cabling</b>	Cable type:	Either single mode or multimode;
		Maximum distance:	
		• 550m for Multimode	
	• 10km for Singlemode		
	Fiber type	Both	
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

### Accessory Product Details

<b>HP X125 1G SFP LC LH40 1310nm Transceiver</b> (JD061A)	<b>Ports</b>	1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)
	<b>Connectivity</b>	Connector type LC
A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.	<b>Physical characteristics</b>	Wavelength 1310 nm
		Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Electrical characteristics</b>	Full configuration weight 0.04 lb. (0.02 kg)
		Power consumption typical 0.8 W
		Power consumption maximum 1.0 W
	<b>Cabling</b>	Cable type: Single-mode fiber optic, complying with ITU-T G.652;
		Maximum distance:
		<ul style="list-style-type: none"> <li>40km distance</li> </ul>
	<b>Services</b>	Fiber type Single Mode
		Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>HP X120 1G SFP LC LH40 1550nm Transceiver</b> (JD062A)	<b>Ports</b>	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)
	<b>Connectivity</b>	Connector type LC
A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.	<b>Physical characteristics</b>	Wavelength 1550 nm
		Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Electrical characteristics</b>	Full configuration weight 0.04 lb. (0.02 kg)
		Power consumption typical 0.8 W
		Power consumption maximum 1.0 W
	<b>Cabling</b>	Cable type: Single-mode fiber optic, complying with ITU-T G.652;
		Maximum distance:
		<ul style="list-style-type: none"> <li>40km distance</li> </ul>
	<b>Services</b>	Fiber type Single Mode
		Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

#### HP X125 1G SFP LC LH70 Transceiver (JD063B)

A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.

<b>Ports</b>	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)
<b>Connectivity</b>	<b>Connector type</b> LC
<b>Physical characteristics</b>	<b>Wavelength</b> 1550 nm
<b>Electrical characteristics</b>	<b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
<b>Cabling</b>	<b>Full configuration weight</b> 0.04 lb. (0.02 kg)
<b>Services</b>	<b>Power consumption typical</b> 0.8 W
	<b>Power consumption maximum</b> 1.0 W
	Cable type: Single-mode fiber optic, complying with ITU-T G.652;
	Maximum distance: • 70km
	Fiber type Single Mode
	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP X120 1G SFP LC BX 10-U Transceiver (JD098B)

A small form-factor pluggable (SFP) Gigabit LX-BX10-U transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.

<b>Ports</b>	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only
<b>Connectivity</b>	<b>Connector type</b> LC
<b>Physical characteristics</b>	<b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
<b>Electrical characteristics</b>	<b>Full configuration weight</b> 0.04 lb. (0.02 kg)
<b>Cabling</b>	<b>Power consumption typical</b> 0.8 W
<b>Notes</b>	<b>Power consumption maximum</b> 1.0 W
<b>Services</b>	Maximum distance: • 10km
	Fiber type Single Mode
	TX 1310nm RX 1490nm
	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

<p><b>HP X120 1G SFP LC BX10-D Transceiver (JD099B)</b></p> <p>A small form-factor pluggable (SFP) Gigabit LX-BX10-D transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.</p>	<b>Ports</b>	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only		
	<b>Connectivity</b>	<b>Connector type</b>	LC	
	<b>Physical characteristics</b>	<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	<b>Electrical characteristics</b>	<b>Full configuration weight</b>	0.04 lb. (0.02 kg)	
		<b>Power consumption typical</b>	0.8 W	
		<b>Power consumption maximum</b>	1.0 W	
	<b>Cabling</b>	Maximum distance:		
		• Up to 10km		
		Fiber type	Single Mode	
	<b>Notes</b>	TX 1490nm RX 1310nm		
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.			

<p><b>HP MSR 1-port ADSL over ISDN SIC Module (JG056B)</b></p>	<b>Notes</b>	This module only provide ISDN U interface	
	<b>Services</b>	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

<p><b>HP MSR 8-port Async Serial SIC Module (JF281A)</b></p>	<b>Connectivity</b>	<b>Bit rate</b>	115.2Kbps
		<b>Interface</b>	RS232
	<b>Services</b>	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

To learn more, visit: [www.hp.com/networking](http://www.hp.com/networking)

© Copyright 2010-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.